SAFE Transports



Adress: Order no: Safe: Safe: Telephone: HxWxD: Floor no: Kg: We would be grateful if you could send us photos for the individual queries, so we can better plan the transport and installation of your safe. Building type: Fastening: Delached Flat Terraced house Commercial property Access by delivery van and trailer: No Unhindered Sketch enclosed Difficult
Telephone: HxWxD: Floor no: Kg: Floor no: Kg: We would be grateful if you could send us photos for the individual queries, so we can better plan the transport and installation of your safe. Building type: Fastening: Detached Flat Terraced house Commercial property Yes Access by delivery van and trailer: No Unhindered Sketch enclosed Difficult
Floor no: Kg: Ploor no: Kg: We would be grateful if you could send us photos for the individual queries, so we can better plan the transport and installation of your safe. Building type: Fastening: Detached Flat Detached Flat Detached Flat Operation Commercial property Yes Access by delivery van and trailer: No Unhindered Sketch enclosed Difficult
We would be grateful if you could send us photos for the individual queries, so we can better plan the transport and installation of your safe. Building type: Fastening: Detached Flat nouse Terraced house Commercial Yes property No Access by delivery van and trailer: No Unhindered Sketch enclosed Difficult
Building type: Fastening: Detached Flat Terraced house Commercial property house Yes Rear wall (wall thickness min. 150 mm) Access by delivery van and trailer: No Floor Bonding Unhindered Sketch enclosed Difficult Delivery route: On the floor in a wardrobe Ground level Via a ramp Lift maximum load in kg: Obstacles along delivery route: Height from floor in cm: (requires additional support force) Narrow doorways including Narrow doorways including Int, clear dimensions HxW: The safe must be mounted flush with the wall to ensure a secure fitting.
Building type: Fastening: Detached Flat Terraced house Commercial property house Yes Rear wall (wall thickness min. 150 mm) Access by delivery van and trailer: No Floor Bonding Unhindered Sketch enclosed Difficult Delivery route: On the floor in a wardrobe Ground level Via a ramp Lift maximum load in kg: Obstacles along delivery route: Height from floor in cm: (requires additional support force) Narrow doorways including Narrow doorways including Int, clear dimensions HxW: The safe must be mounted flush with the wall to ensure a secure fitting.
Detached Flat Terraced house Commercial property Access by delivery van and trailer: No Floor Bonding Unhindered Sketch enclosed Difficult Delivery route: On the floor in a wardrobe Ground level Via a ramp Lift maximum load in kg: Obstacles along delivery route: Height from floor in cm: (requires additional support force) Marrow doorways including Mounted freely suspended up to max. Business 801 (requires flawless concrete and free installation access) The safe must be mounted flush with the wall to ensure a secure fitting.
house property house property Access by delivery van and trailer: No Unhindered Sketch enclosed Delivery route: On the floor in a wardrobe Ground level Via a ramp Lift maximum load in kg: On the floor in cm: (requires additional support force) Mounted freely suspended up to max. Business 801 (requires flawless concrete and free installation access) The safe must be mounted flush with the wall to ensure a secure fitting.
Unhindered Sketch enclosed Delivery route: Ground level Via a ramp Lift maximum load in kg: Obstacles along delivery route: Height from floor in cm: (requires additional support force) Mounted freely suspended up to max. Business 801 (requires flawless concrete and free installation access) The safe must be mounted flush with the wall to ensure a secure fitting.
Delivery route: On the floor in a wardrobe Ground level Via a ramp Lift maximum load in kg: Obstacles along delivery route: Height from floor in cm: (requires additional support force) Mounted freely suspended up to max. Business 801 (requires flawless concrete and free installation access) The safe must be mounted flush with the wall to ensure a secure fitting.
Ground level Via a ramp Lift maximum load in kg: Wardrobe plinth height cm: Obstacles along delivery route: Height from floor in cm: (requires additional support force) Mounted freely suspended up to max. Business 801 (requires flawless concrete and free installation access) Narrow doorways including The safe must be mounted flush with the wall to ensure a secure fitting.
Ground level Via a ramp Lift maximum load in kg: Wardrobe plinth height cm: Obstacles along delivery route: Height from floor in cm: (requires additional support force) Narrow doorways including Mounted freely suspended up to max. Business 801 (requires flawless concrete and free installation access) The safe must be mounted flush with the wall to ensure a secure fitting.
Ground level Via a ramp load in kg: Wardrobe plinth height cm: Obstacles along delivery route: Height from floor in cm: (requires additional support force) Mounted freely suspended up to max. Business 801 (requires flawless concrete and free installation access) Narrow doorways including lift, clear dimensions HxW: The safe must be mounted flush with the wall to ensure a secure fitting.
Narrow doorways including Ift, clear dimensions HxW: Mounted freely suspended up to max. Business 801 (requires flawless concrete and free installation access) The safe must be mounted flush with the wall to ensure a secure fitting.
Narrow doorways including (requires flawless concrete and free installation access) Ift, clear dimensions HxW: The safe must be mounted flush with the wall to ensure a secure fitting.
Iff, clear dimensions HxW:
The balle model be meaned math with the walk to bload a boot of many.
Height Clear dimensions with a rear wall frame. If mounting at height in a wardrobe, the rear wall of the wardrobe must be cut out and the load capacity of the shelf (made
Roof projection HxW: Internal sill by a carpenter) must be able to support the weight of the safe. If
Distance to street in m: height: mounting on the floor in a wardrobe, the floor cavity must also be supported.
Our fitters will decide how feasible this is on site.
Skirting board: Stone Wood
Stairs: Sketch enclosed Sketch enclosed Skirting board height in cm:
Banister / hand rail Removable
90° turn 180° turn Concrete Brick Wood Plaster Ytong Quarry Don't know
No. of flights of stairs:
Staircase width in cm: Underfloor yes no Don't know heating:
No. of steps: The customer is responsible for any damage to any hidden electricity cables, water pipes, etc. No claims for compensation will be accepted.
Step height in cm : Step
width in cm : Landing Other information: Photos / Sketches:
depth in cm: Landing
width in cm: Stair
covering / material: Step shape:

SWISS MADE

WALDIS Tresore AG

Hofwisenstrasse 20 CH-8153 Rümlang

I

Tel. +41 43 211 12 00 Fax +41 43 211 12 12

info@tresore.ch www.tresore.ch